

WHEELCHAIR ACCESSIBLE WATER COOLER



The thirst quenchers!



- Wheelchair accessible
- Light-touch front and side push bars
- Environmentally friendly r134a refrigerant
- Stainless steel basin with integral drain
- Food grade stainless steel water reservoir
- Flexiguard safety bubbler tap (prevents accidental mouth injuries)
- Low energy consumption
- 1 Year comprehensive warranty
- 25 Litres per hour cooling capacity
- Can be wall mounted at any height to suit any application



WHEELCHAIR ACCESSIBLE WATER COOLER

GENERAL FEATURES

ACCESSIBILITY:

Our Waterworks wheelchair accessible wall mounted water cooler is designed to provide easy access to a refreshing drink of water for adults, children and wheelchair bound people alike. It's unique design and the ability to be mounted onto the wall at any height, make this the ideal water cooler for any application, including commercial, educational, public access, and special needs areas.

LIGHT TOUCH ACTIVATION:

Highly visible, self closing push bars on the front and both sides. An internal regulator provides a steady water stream with any mains water pressure from 140 to 700Kpa.

STAINLESS STEEL CABINET:

Both the cabinet panels and the one piece top are constructed from high grade stainless steel. This extremely strong material provides both significant structural integrity and vandal resistance.

INSTALLATION

ELECTRICAL:

A 1.2 Metre cordset with 3 pin plug is provided. The wheelchair accessible water coolers do not have any specialised power requirements and can be plugged into any 240V 50Hz single phase GPO.

Installation of your water cooler must only be carried out by a licensed technician and all aspects of the installation must comply with the current local authority standards and regulations. Connection should only be made to potable, municipal water supply and must always include an isolation tap to allow periodic maintenance, service work and filter changes to be performed. The operating pressure of the wheelchair accessible unit ranges between 140-700Kpa.

LOCATION:

Your wheelchair accessible water chiller is an electrical appliance and as such should be placed in an area protected from the elements and any external water sources.

The unit should be placed onto a firm wall, with the base of the unit no lower than 230mm, and the top of the faucet no higher than 915mm.

The water cooler is fitted with a 1.5M power cord which connects to any standard 240V 1PH 50Hz power outlet.

PLUMBING:

The universal design of these water coolers allows for easy retrofit over existing plumbing connections.

Internal fittings include a 3/8" female threaded inlet and a 32mm drain outlet.

PERFORMANCE

ROOM TEMP °C	21	27	32	38
COOLING LITRES PER HOUR	30L	27L	25L	20L

**Intermittent use only, continuous use will result in reduced performance.*

CAPACITIES:

MODEL	Wheelchair Accessible
AMBIENT TEMPERATURE	27°
LITRES PER HOUR 10° WATER	40
RESERVOIR VOLUME	1.8L

SHIPPING WEIGHTS & DIMENSIONS:

WIDTH	HEIGHT	LENGTH	WEIGHT	VOLTAGE
48.3cm	50cm	46cm	23.2kg	220



Distributed by...

Waterworks Australia

ABN 91 902 793 936

48 Neumann Road Capalaba Queensland 4157

Phone (07) 3390 3777 • Fax (07) 3390 1766

Email sales@waterworksaustralia.com

www.waterworksaustralia.com

As part of Waterworks Australia's policy of continuous improvement, we reserve the right to alter specifications at anytime without notice.